

Plan XV - length 550



OUTPUT IN WATTS AT A TEMPERATURE SET OF 90°/70°/20°C

Height	Depth = 86 (type 21)	Depth = 116 (type 22)	Depth = 173 (type 33)
1600	1375	1739	2507
1700	1439	1819	2629
1800	1494	1887	2731
1900	1693	2102	3039
2000	1757	2180	3158
2100	1801	2236	3242
2200	1851	2302	3340
2300	1838	2308	3338
2400	1885	2369	3429
2500	1931	2429	3516
2600	1918	2437	3517
2700	1968	2499	3610
2800	2024	2569	3715
2900	2247	2795	4056
3000	2252	2822	4085

Subject to technical modifications and typographical errors – and to changes in the product range. Find the latest updates on www.hudevad.com.

Plan XV - length 650



OUTPUT IN WATTS AT A TEMPERATURE SET OF 90°/70°/20°C

Height	Depth = 86 (type 21)	Depth = 116 (type 22)	Depth = 173 (type 33)
1600	1719	2174	3134
1700	1799	2274	3287
1800	1868	2359	3413
1900	2117	2628	3799
2000	2196	2725	3947
2100	2251	2795	4052
2200	2314	2877	4175
2300	2297	2885	4172
2400	2356	2961	4286
2500	2413	3037	4395
2600	2398	3046	4397
2700	2460	3124	4513
2800	2530	3211	4644
2900	2809	3494	5070
3000	2815	3527	5106

Subject to technical modifications and typographical errors – and to changes in the product range. Find the latest updates on www.hudevad.com.

Plan XV - length 750



OUTPUT IN WATTS AT A TEMPERATURE SET OF 90°/70°/20°C

Height	Depth = 86 (type 21)	Depth = 116 (type 22)	Depth = 173 (type 33)
1600	2063	2608	3761
1700	2159	2729	3944
1800	2241	2830	4096
1900	2540	3153	4559
2000	2635	3269	4737
2100	2701	3354	4863
2200	2777	3453	5010
2300	2757	3462	5007
2400	2828	3553	5143
2500	2896	3644	5274
2600	2877	3656	5276
2700	2952	3749	5415
2800	3037	3853	5573
2900	3371	4192	6084
3000	3378	4232	6127

Subject to technical modifications and typographical errors – and to changes in the product range. Find the latest updates on www.hudevad.com.

Plan XV - length 850



OUTPUT IN WATTS AT A TEMPERATURE SET OF 90°/70°/20°C

Height	Depth = 86 (type 21)	Depth = 116 (type 22)	Depth = 173 (type 33)
1600	2406	3043	4388
1700	2519	3184	4602
1800	2615	3302	4778
1900	2963	3679	5319
2000	3074	3814	5526
2100	3151	3914	5673
2200	3240	4028	5845
2300	3216	4039	5841
2400	3299	4145	6001
2500	3378	4251	6153
2600	3357	4265	6155
2700	3444	4373	6318
2800	3543	4495	6502
2900	3932	4891	7098
3000	3940	4938	7148

Subject to technical modifications and typographical errors – and to changes in the product range. Find the latest updates on www.hudevad.com.

Plan XV - length 950



OUTPUT IN WATTS AT A TEMPERATURE SET OF 90°/70°/20°C

Height	Depth = 86 (type 21)	Depth = 116 (type 22)	Depth = 173 (type 33)
1600	2750	3478	5015
1700	2879	3638	5259
1800	2989	3774	5461
1900	3386	4204	6079
2000	3513	4359	6316
2100	3601	4473	6484
2200	3703	4604	6680
2300	3676	4616	6676
2400	3770	4738	6858
2500	3861	4858	7032
2600	3836	4874	7035
2700	3936	4998	7220
2800	4049	5137	7431
2900	4494	5590	8112
3000	4503	5643	8170

Subject to technical modifications and typographical errors – and to changes in the product range. Find the latest updates on www.hudevad.com.

Plan XV - length 1050



OUTPUT IN WATTS AT A TEMPERATURE SET OF 90°/70°/20°C

Height	Depth = 86 (type 21)	Depth = 116 (type 22)	Depth = 173 (type 33)
1600	3094	3913	5642
1700	3239	4093	5916
1800	3362	4245	6144
1900	3810	4730	6838
2000	3953	4904	7105
2100	4051	5032	7294
2200	4166	5179	7515
2300	4135	5193	7510
2400	4242	5330	7715
2500	4344	5466	7911
2600	4316	5484	7914
2700	4428	5623	8123
2800	4555	5779	8360
2900	5056	6289	9126
3000	5066	6348	9191

Subject to technical modifications and typographical errors – and to changes in the product range. Find the latest updates on www.hudevad.com.

Plan XV - length 1150



OUTPUT IN WATTS AT A TEMPERATURE SET OF 90°/70°/20°C

Height	Depth = 86 (type 21)	Depth = 116 (type 22)	Depth = 173 (type 33)
1600	3438	4347	6268
1700	3599	4548	6574
1800	3736	4717	6826
1900	4233	5255	7598
2000	4392	5449	7895
2100	4502	5591	8105
2200	4628	5755	8350
2300	4595	5770	8345
2400	4713	5922	8572
2500	4826	6073	8791
2600	4796	6093	8793
2700	4920	6248	9025
2800	5061	6421	9288
2900	5618	6987	10140
3000	5629	7054	10212